

USA / Canada / Mexico - Dual Voltage Receptacles

Dual Voltage Straight Blade Receptacles



Product Features

- **Grounding:** Self Grounding
- **Feature:** Dual Voltage
- **Amperage:** 15, or 20 Amp.
- **Voltage:** 125/250 Volt
- **NEMA:** 5-15R and 6-15R
- **Poles/Wires:** 2 Pole, 3 Wire
- **Termination:** Side, Back & Side
- **Face Material:** Nylon
- **Body Material:** Nylon
- **Strap Material:** Zinc-Plated Steel
- **Standards:** NEMA WD-6; ANSI C-73; UL498; CSA C22.2 No. 42
- **Certifications:** UL File E13399; CSA File 152105; NOM 057



Catalog No.*	Rating	Description
5031	15A	Dual Voltage Receptacle, Commercial Grade, Side Wired
5292	15A	Dual Voltage Receptacle, UL Fed Spec WC-596, Back & Side Wired
5842	20A	Dual Voltage Receptacle, Commercial Grade, Side Wired
5844	20A	Dual Voltage Receptacle, UL Fed Spec WC-596, Back & Side Wired

* Colors available: Brown, (-I) Ivory, Catalog No. 5031 also (-W) White

AC Horsepower Ratings

At Rated Voltage: 1/2 HP 125V / 1-1/2 HP 250V at 15 Amp.
1 HP 125V / 2 HP 250V at 20 Amp.

Electrical Specifications

Dielectric Voltage: Withstands 2000V per UL498
Current Limiting: Full Rated Current
Temperature Rise: 30°C max at full rated current after 100 cycles overload at 150% (after 250 cycles overload at 200%) rated current for both AC and DC per UL 498

Environmental Specifications

Flammability: Rated V-2 per UL94
Operating Temperature: -40°C to +60°C

Material Specifications

Face Material: Nylon
Body Material: Nylon
Line Contacts: Brass Triple-Wipe
Terminal Screws: Brass 10-32 (8-32)
Grounding Screw: Brass 8-32
Yoke: Zinc-Plated Steel
Ground Clips: Brass-Plated

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground, White-Neutral
Terminal Accom.: #14 - #10 AWG
Product ID: Ratings are permanently marked on device

