




UL CSA

**SPECIFICATIONS**

- Base, High Impact Thermoplastic, 125°C
- Class J Holders Have been Tested and Approved for 200,000 Amp Interrupting Capacity
- Patented Cool Clip® Design
- Clip, Copper Alloy, Tin Plated
- UL Listed and CSA Certified
- Reinforcing Member Available
- Integral DIN Rail Mount
- Slotted Mounting Hole
- Expander Block Available upon Request

Wire Connectors: S  SP  B 

Class J Fuse Holders 600Vac 0-30Amp

Fuse Size: (Ø 20.6 x 57.2)mm

No. of Poles	Cat.No. Class J Standard	Reinforced	Wire Connector	Copper Wire Range (AWG)	UPE Packed
1	6J 30A 1S	R6J 30A 1S	Screw	10 - 22	50
2	6J 30A 2S	R6J 30A 2S	Screw	10 - 22	25
3	6J 30A 3S	R6J 30A 3S	Screw	10 - 22	20
Expander	6J 30A ES	R6J 30A ES	Screw	10 - 22	50
1	6J 30A 1SP	R6J 30A 1SP	Sems Pressure	10 - 14	50
2	6J 30A 2SP	R6J 30A 2SP	Sems Pressure	10 - 14	25
3	6J 30A 3SP	R6J 30A 3SP	Sems Pressure	10 - 14	20
Expander	6J 30A ESP	R6J 30A ESP	Sems Pressure	10 - 14	50
1	6J 30A 1B	R6J 30A 1B	Box	6 - 14	50
2	6J 30A 2B	R6J 30A 2B	Box	6 - 14	25
3	6J 30A 3B	R6J 30A 3B	Box	6 - 14	20
Expander	6J 30A EB	R6J 30A EB	Box	6 - 14	50