


Dimensions  
= mm



Amp	Series	A	B	C	D	E	F	G
0 - 30	NLN/NLKP	50.8	12.7	12.7	14.3	-	-	-
	NLS	127.0	19.1	15.9	20.6	-	-	-
35 - 60	NLN/NLKP	76.2	19.1	15.9	20.6	-	-	-
	NLS	139.7	25.4	15.9	27.0	-	-	-
70 - 100	NLN	149.2	25.4	25.4	27.0	3.2	19.1	33.3
	NLS	200.0	31.8	25.4	33.3	3.2	19.1	39.7
110 - 200	NLN	181.0	38.1	34.9	39.7	4.8	28.6	47.6
	NLS	244.5	44.5	34.9	46.8	4.8	28.6	53.2
225 - 400	NLN	219.1	50.8	47.6	53.2	6.4	41.3	61.1
	NLS	295.3	63.5	47.6	65.9	6.4	41.3	73.0
450 - 600	NLN	263.5	63.5	57.2	65.9	6.4	50.8	73.0
	NLS	339.7	76.2	57.2	78.6	6.4	50.8	87.3

**NLN/NLS "ONE-TIME" Class K5 Fuses**

Fast-Acting / flink  
 NLN/NLS UL Listed Class K5 (UL 198D)  
 NLKP UL Listed Class H (UL 198D)  
 NLN/NLS/NLKP CSA Certified per 59.1  
 (CSA Excluding NLN 15-60A)

**Voltage Ratings**

AC: 250 Volts (NLN, NLKP)  
 600 Volts (NLS)  
 DC: 250 Volts (NLN)  
 400 Volts (NLS 35-60A)  
 500 Volts (NLS 8-15A, 225-600A)  
 600 Volts (NLS 1-7, 20-30, 70-200A)

Catalog No's	Rated Current / Nennstrom 1 - 600 Amperes											UPE/Packed
	1	2	3	4	5	6	7	8	10	12		
NLN,NLS												10
NLN,NLKP,NLS	15	20	25	30	35	40	45	50	60			10
NLN,NLS	70	80	90	100								5
NLN,NLS	110	125	150	175	200	225	250	300	350	400		1
	450	500	600									