

Europe

Appliance sockets and appliance connectors, DIN EN 60320 (16A, 250V~, 2P + E)

Appliance sockets and appliance connectors, rewirable (straight and angled), also versions for flange mounting or panel mounting, IEC 60320 (C19/C20, I/J).

FEATURES

- Rewirable appliance plugs and connectors
- Flange or panel mounting inlets and outlets
- 70°C, 16 Amp, 250 Volt AC
- 2-Pole 3-Wire Grounding (2P + E)
- VDE, CE, RoHS, ENEC 10
- Standard color: Black "BK" (Polyamide)
Further colors available (Gray "GR" or White "WH" etc.) depending on quantities, contact our sales office.

Visit our Website: www.biaonline.com
for Data Sheets and further Informations

ORDERING INFORMATION

(Catalog numbers shown for black versions only.)



Catalog No.	Description	Net Weight	VPE / Pack
736BK	Appliance socket 70°C, black, Screw Terminals, angled cable entry (right)	0.035 kg	100/20
737BK	Appliance socket 70°C, black, Screw Terminals, angled cable entry (left)	0.035 kg	100/20
763BK	Appliance socket 70°C, black, Screw Terminals, straight cable entry	0.036 kg	100/25
745BK	Appliance plug 70°C, black, Screw Terminals, angled cable entry (left)	0.036 kg	100/20
746BK	Appliance plug 70°C, black, Screw Terminals, angled cable entry (right)	0.036 kg	100/20
765BK	Appliance plug 70°C, black, Screw Terminals, straight cable entry	0.037 kg	100/25
766BK	Appliance outlet 70°C, black, Screw Terminals, Screw Mounting	0.026 kg	100/25
766BKxx	Appliance outlet 70°C, black, Tab terminals, Screw Mounting, (Suffix Tab terminals: 48 = 4.8mm, 63 = 6.3mm)	0.020 kg	100/25
766RBK0xx	Appliance outlet 70°C, black, Screw Terminals, Snap-In Mounting, (Suffix Panel Thickness: 10 = 1.0mm, 16 = 1.6mm)	0.020 kg	100/25
766RBK4xx	Appliance outlet 70°C, black, Tab terminals 4.8mm, Snap-In Mounting, (Suffix Panel Thickness: 10 = 1.0mm, 16 = 1.6mm)	0.016 kg	100/25
766RBK6xx	Appliance outlet 70°C, black, Tab terminals 6.3mm, Snap-In Mounting, (Suffix Panel Thickness: 10 = 1.0mm, 16 = 1.6mm)	0.016 kg	100/25
767BK	Appliance inlet 70°C, black, Screw Terminals, Screw Mounting	0.018 kg	200/50
767BKxx	Appliance inlet 70°C, black, Tab terminals, Screw Mounting, (Suffix Tab terminals: 48 = 4.8mm, 63 = 6.3mm)	0.014 kg	200/50
767RBK0xx	Appliance inlet 70°C, black, Screw Terminals, Snap-In Mounting, (Suffix Panel Thickness: 10 = 1.0mm, 16 = 1.6mm, 25 = 2.5mm)	0.017 kg	200/50
767RBK4xx	Appliance inlet 70°C, black, Tab terminals 4.8mm, Snap-In Mounting, (Suffix Panel Thickness: 10 = 1.0mm, 16 = 1.6mm, 25 = 2.5mm)	0.013 kg	200/50
767RBK6xx	Appliance inlet 70°C, black, Tab terminals 6.3mm, Snap-In Mounting, (Suffix Panel Thickness: 10 = 1.0mm, 16 = 1.6mm, 25 = 2.5mm)	0.013 kg	250/50

Technical data and informations are nominal only and subject to change without notice. Dimensions in mm.