

Product Information

PERILEX Plug Connection System

3-Pole + N + PE, 16 Amp, 400/230 Volt AC, according to DIN 49445 / 49446

Description

PERILEX is the tradename for an old German three-phase indoor electric power connector system, still used in Germany, Sweden and The Netherlands for special applications.

The originally versions are manufactured 16A (with horizontal grounding pin) and 25A (with vertical grounding pin. Some of these old products are still available.

Contact our sales office for availability.

Specifications

• Rated current: 16 Amp max • Rated voltage: 400/230V AC

• 3-Pole + N (neutral) + PE (ground) • Applicable standards: DIN 49445/46 Approvals: VDE, SEMKO, KEMA




Ordering Information

| Catalog Number | Product Description | Net Weight each (kg) | Standard Pack* |
|-------------------|---|-------------------------|-------------------|
| 2201110 | Plug, 16A, 400/230Vac, 3P+N+PE, Thermoset, white, DIN 49445/46 | 0.099 | 100/10 |
| 2407110 | Angle Plug, 16A, 400/230Vac, 3P+N+PE, Thermoset, white, DIN 49445/46 | 0.113 | 100/10 |
| 2206110 | Connector, 16A, 400/230Vac, 3P+N+PE, Thermoset, white, DIN 49445/46 | 0.149 | 100/10 |
| 2421110 | Flush Mounting Socket Outlet, 16A, 400/230Vac, 3P+N+PE, white, DIN 49445/46 | 0.152 | 100/10 |
| 2451510 | Flush Mounting Socket Outlet IP44 with Box, 16A, 400/230Vac, 3P+N+PE, white, DIN 49445/46 | 0.234 | 100/10 |
| 2491010 | Surface Mounting Socket Outlet, 16A, 400/230Vac, 3P+N+PE, white, DIN 49445/46 | 0.136 | 100/10 |
| 2441860 | Surface Mounting Socket Outlet IP44, 16A, 400/230Vac, 3P+N+PE, grey, DIN 49445/46 | 0.271 | 50/5 |

^{*} Non stock products have a minimum order quantity.

Dimensions



B-I-A Vertriebs GmbH / Germany

Email: info@biaonline.com





2491010







Specifications subject to change. For complete specifications and availability, visit www.biaonline.com