

Industrial Grade Locking Devices 30A 277V; 30A 480V



NEMA
L7-30P



NEMA
L7-30R



NEMA
L8-30P



NEMA
L8-30R



2641



2643



2630



2640-IG



2645



2646

Description	Plug	Connector	Single Flush Receptacle	Single Flush IG Receptacle	Flanged Inlet	Flanged Outlet
30A 277V, NEMA L7-30P AND L7-30R, 2-P 3-W, Grounding						
Black & White	2631	2633	—	—	—	—
All Black	—	—	2630	—	—	—
All White	—	—	—	—	2635	2636
Orange	—	—	—	2630-IG	—	—
Power Indication Black & White	2631-PLC	2633-PLC	—	—	—	—
30A 480V, NEMA L8-30P AND L8-30R, 2-P 3-W, Grounding						
Black & White	2641	2643	—	—	—	—
All Black	—	—	2640	—	—	—
All White	—	—	—	—	2645	2646
Orange	—	—	—	2640-IG	—	—

ELECTRICAL		
DIELECTRIC VOLTAGE	CURRENT INTERRUPT.	TEMP. RISE
Withstands 2000V per UL 498	Full rated current	Max 30°C after 250 cycles of overload at 200% of rated current

MECHANICAL			
TERMINAL I.D.	TERMINAL ACCOMM.	PRODUCT I.D.	CORD GRIP RANGE
Brass, hot	#18 - #10 AWG	Ratings & NEMA I.D. permanently marked on device	.385" - .860"
Grounding White, neutral	Receptacles #14 - #8 AWG		
ENVIRONMENTAL			
FLAMMABILITY		OPERATING TEMP.	
Rated V-2 per UL 94		Receptacles Rated V-0 per UL 94	
-40°C to 60°C			

STANDARDS & CERTIFICATIONS					
NEMA WD-6	ANSI C-73	UL 498	UL Fed Spec Listed WC-596	CSA C22.2 No.42	NOM
✓	✓	✓	#E13393 Plugs, Connectors & Flanged Inlets	#LR-406	#057
			#E13399 Receptacles & Flanged Outlets		

ACCESSORIES

<p>Thermoplastic Elastomer Boots</p> <p>Connector Boot 6032 (Black) 6032-Y (Yellow)</p>	<p>Plug Boot 6031 (Black) 6031-Y (Yellow)</p>	<p>Flip Lid Cover, IP64 Includes Gasket & Screws, For Inlets and Outlets WP2 (Gray Lexan)</p>	<p>Cover (Self-Closing Lid) Weather-Resistant, For Single Receptacles 4980-GY (Gray Plastic)</p>
			<p>Flip Lid Cover, IP64 Includes Gasket & Screws, For Receptacles 7420-CR (Yellow Lexan)</p>