

Catalog #: 2716

Description: 30 Amp, 125/250 Volt, NEMA L14-30R, 3P, 4W, Flanged Outlet Locking Receptacle, Industrial Grade, Grounding, - White

INDUSTRIAL GRADE

LIFETIME WARRANTY

Product Features:

- Ground: Grounding
- Amperage: 30 Amp
- Voltage: 125/250 Volt
- NEMA: L14-30R
- Pole: 3
- Wire: 4
- Termination: Back
- Face Material: Nylon
- Body Material: Nylon
- Strap Material: Thermoplastic Nylon
- Color: White
- Standards and Certifications: UL/CSA



L14-30R

Device Color



White

Electrical Specifications	
Dielectric Voltage	Withstands 2000V per UL498
Current Limiting	Full Rated Current
Temperature Rise	Max 30C after 250 cyc OL at 200 pct rated current

Mechanical Specifications	
Terminal ID	Brass-Hot, Green-Ground, White-Neutral
Terminal Accom.	14-8 AWG
Product ID	Ratings and NEMA I.D. permanently marked on device

Material Specifications	
Face Material	Nylon
Body Material	Nylon
Line Contacts	Brass .035 Thick
Terminal Screws	Brass 10-32
Grounding Screw	Brass 8-32

Environmental Specifications	
Flammability	Rated V-2 per UL94
Operating Temp.	-40C to 60C

AC Horsepower Ratings	
At Rated Voltage	2 HP L-L / 2 HP L-N

Standards and Certifications	
NEMA	WD-6
ANSI	C-73
UL498	File E13399
UL Fed Spec WC-596	File E13399
CSA C22.2 No. 42	File LR-406
NOM	057

