

**5374**


**Catalog #:** 5374

**Description:** 50 Amp, 250 Volt, NEMA 6-50R, 2P, 3W, Flush Mtg Receptacle, Straight Blade, Industrial Grade, Grounding, , Side Wired, Steel Strap, - Black

**INDUSTRIAL GRADE**

**5374  
Series**

**Product Features:**



6-50R  
Device Color



Black

- Ground: Grounding
- Amperage: 50 Amp
- Voltage: 250 Volt
- NEMA: 6-50R
- Pole: 2
- Wire: 3
- Termination: Side
- Face Material: Nylon
- Body Material: Nylon
- Strap Material: Steel
- Color: Black
- Standards and Certifications: UL/CSA

**Technical Information**

Electrical Specifications	
Dielectric Voltage	Withstands 2000V per UL498
Current Limiting	Full Rated Current
Temperature Rise	Max 30C after 50 cyc OL at 150 pct rated current

Material Specifications	
Face Material	Nylon
Body Material	Nylon
Line Contacts	Brass Double-Wipe
Product ID	Ratings are permanently marked on device
Yoke	Zinc-Plated Steel

AC Horsepower Ratings	
At Rated Voltage	3 HP

Mechanical Specifications	
Terminal ID	Brass-Hot, Green-Ground, White-Neutral
Terminal Accom.	Up to 4 AWG

Environmental Specifications	
Flammability	Rated V-2 per UL94
Operating Temp.	-40C to 60C

Standards and Certifications	
NEMA	WD-6
ANSI	C-73
UL498	File E13399
CSA C22.2 No. 42	File 152105
NOM	057