

SmartLock® Advanced GFCI Receptacles

SmartLock®, the First Advanced Technology GFCI to Take People Protection to a Higher Level



Thick-walled, impact-resistant thermoplastic nylon cover and body withstand abuse

Silver alloy contacts for reliable switching

Triple combination termination screws

Advanced electronic design offers superior resistance to surges and overvoltages

Heavy-duty contacts are double wipe for 15 Amp and triple wipe for 20 Amp

Patented lockout feature prevents "RESET" if GFCI is not functioning properly or miswired due to reversal of line and load leads

LED power indicator light on lighted models helps diagnose improper wiring and, when illuminated, offers visual confirmation that power is available

Eight back-wired holes (two for each terminal) provide maximum wiring capability




Look for the Lock when choosing a GFCI. The lock ensures improved GFCI performance



Lockout action blocks the "RESET" button if GFCI protection has been compromised



Optional LED indicator offers visual confirmation of power availability



Advanced electronics design provides superior resistance to electrical surges and over-voltages

Offers a Choice of TEST and RESET Button Color

Every GFCI receptacle is required by UL to have "TEST" and "RESET" buttons, providing a simple, clear means of testing whether the device is operating properly. These GFCIs are available in two versions to meet your needs. One version has matching body color (monochromatic) buttons, offering a stylish, unobtrusive appearance. The other version has a traditional **black** TEST button and a **red** RESET button, which is ideal in applications where fast, easy identification of the GFCI is desired.

Agency Standards

- Meets or exceeds all new UL requirements for January 1, 2003
- UL Standard 943 Class A (GFCI) and 498 (Receptacles)
- UL Listed (File #E-48380) • CSA Certified (File #LR-57811)
- NOM Certified (File #057)

Catalog No.: 8599-I

Description: 15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Decora Plus Duplex Receptacle, Straight Blade, Commercial Grade, GFCI Ground Fault, SmartLock GFCI, Back & Side Wired, Steel Strap, - Ivory



Product Features:

- Grounding: GFCI Ground Fault
- Features: SmartLock GFCI
- Amperage: 15 Amp
- Voltage: 125 Volt
- NEMA: 5-15R
- Pole: 2
- Wire: 3
- Termination: Back & Side
- Face Material: Thermoplastic Nylon
- Body Material: Thermoplastic Nylon
- Strap: Steel
- Color: Ivory
- Standards And Certifications: UL/CSA
- Warranty: 2-Year Limited



15A SmartLock Advanced GFCI
Catalog No's. 8598 / 8599

All Single-Gang Standard Size Wallplates

