

VAN GOGH® LIGHTING CONTROLS • 800–2000 WATTS • 120V AC 60Hz Commercial Grade Lighting Controls



Van Gogh Architectural Specification Rotary Dimmers


Van Gogh Incandescent 120V AC 60Hz Only (9) 69-

DESCRIPTION	CAT. NO.	RATING	COLOR*	
Van Gogh Single-Pole Rotary (narrow fin)	60800	W008	I, W	
Van Gogh 3-Way Push ON/Push OFF (narrow fin)	60800-3	W008	I, W	
Van Gogh Single-Pole Rotary (narrow fin)	61000	1000W	I, W	
Van Gogh 3-Way Push ON/Push OFF (narrow fin)	61000-3	1000W	I, W	
Van Gogh Single-Pole Rotary (wide fin)	61500	1500W	I, W	
Van Gogh Single-Pole Rotary (wide fin)	62000	2000W	I, W	

Note: Sharing a neutral wire may cause flickering. Connect all dimmers to the same phase or run a separate neutral to each phase. Consult Techline if problems persist.

When ganging these units, no derating is necessary except on those units which have had both sets of snap-off, fins removed. These shall be derated as follows:

Maximum Load per Van Gogh Dimmer Multi-Gang with Fins Broken Off				
Cat. No.	Single	2-Gang	More Than 2-Gang	
60800	800W	700W	600W	
61000	1000W	800W	700W	
61500	1500W	1300W	1100W	
62000	2000W	1800W	1500W	



Color Change Kits for 60800, 61000 Dimmer Units

DESCRIPTION	CAT. NO.
Brown Cover and Matching Knob w/Gold Insert	60001
Ivory Cover and Matching Knob w/Gold Insert	60001-I
White Cover and Matching Knob w/ Silver Insert	60001-W

Color Change Kits for 61500, 62000 Dimmer Units

DESCRIPTION	CAT. NO.
Brown Cover and Matching Knob w/Gold Insert	60002
Ivory Cover and Matching Knob w/Gold Insert	60002-I
White Cover and Matching Knob w/ Silver Insert	60002-W

Van Gogh™ Architectural Rotary Fan Speed Control 120V AC 60Hz Only

DESCRIPTION	CAT. NO.	RATING	COLOR*
Van Gogh Single-Pole (wide fin)	61027	10 Amps	I, W

Note: When more than one ceiling fan is controlled, make sure the blades are rotating on all fans.

Van Gogh Architectural Fin Width Narrow: 2.75" (69.9 mm) Wide: 4.56" (115.8 mm)

SPECIFICATIONS AND FEATURES

- Classic rotary architectural-style dimmer is a popular choice in many installations
- Available in Rotary ON/OFF (single pole only) and Push-ON/Push-OFF (3-way).
- 3-way version is used with a standard 3-way ON/OFF switch
- · Snap-on cover conceals heat fins
- Color-matched dimmer control knob with gold insert for an attractive appearance in any installation
- $\bullet\,$ Snap-off fins permit easy ganging with other devices
- Slim, compact housing easily fits in standard wall box
- Large radio/TV interference filter

TESTING AND CODE COMPLIANCE

- UL Listed (File #E-31373, 62000 File #E-66800)
- CSA Certified (File #LR-3413)
- · Backed by a Limited Five-Year Warranty

*COLOR

Add suffix to catalog number as follows for colors: lvory cover with Gold insert (-I), White cover with Silver insert (-W).

MATERIAL CHARACTERISTICS

Environmental: Flammability UL-94, V2 Rating Operating Temperature: 32°F to 130°F