

278

Catalog #: 278

Description: 30 Amp, 125/250 Volt, NEMA 14-30R, 3P, 4W, Flush Mtg Receptacle, Straight Blade, Industrial Grade, Grounding, , Side Wired, Steel Strap, - Black

INDUSTRIAL GRADE

278 Series

Product Features:



14-30R
Device Color



Black

- Ground: Grounding
- Amperage: 30 Amp
- Voltage: 125/250 Volt
- NEMA: 14-30R
- Pole: 3
- Wire: 4
- Termination: Side
- Face Material: Nylon
- Body Material: Nylon
- Strap Material: Steel
- Color: Black
- Standards and Certifications: UL/CSA

Electrical Specifications	
Dielectric Voltage	Withstands 2000V per UL498
Current Limiting	Full Rated Current
Temperature Rise	Max 30C after 50 cyc OL at 150 pct rated current

Mechanical Specifications	
Terminal ID	Brass-Hot, Green-Ground, White-Neutral
Terminal Accom.	Up to 4 AWG

Material Specifications	
Face Material	Nylon
Body Material	Nylon
Product ID	Ratings are permanently marked on device
Line Contacts	Brass Double-Wipe
Yoke	Zinc-Plated Steel

Environmental Specifications	
Flammability	Rated V-2 per UL94
Operating Temp.	-40C to 60C

AC Horsepower Ratings	
At Rated Voltage	2 HP

Standards and Certifications	
NEMA	WD-6
ANSI	C-73
UL498	File E13399
CSA C22.2 No. 42	File 152105
NOM	057