

## Wetguard 20 Amp. 2-Pole 3-Wire

ELECTRICAL	
<b>DIELECTRIC VOLTAGE</b>	<b>CURRENT INTERR.</b>
Withstands 2000V per UL 498	Full rated current
<b>TEMP. RISE</b>	
Max 30°C after 250 cycles of overload at 200% of rated current	

MECHANICAL											
TERMINAL I.D.	PRODUCT I.D.	DEVICE TYPE			CORD GRIP RANGE						
Brass, hot	Ratings & NEMA I.D. permanently marked on device	15 & 20A Straight Blade & 15A Locking - 3-Wire			(.375" - .655") #18-#10 AWG						
Grounding		20A Locking 3-, 4- & 5-Wire			(.375" - .875") #18-#10 AWG						
White, neutral		30A Locking 3-, 4- & 5-Wire			(.625" - 1.125") #12-#8 AWG						
ENVIRONMENTAL				STANDARDS & CERTIFICATIONS							
<b>FLAMMABILITY</b>		<b>OPERATING TEMP.</b>		<b>NEMA WD-6</b>	<b>ANSI C-73</b>	<b>UL 498</b>	<b>UL Fed Spec Listed WC-596</b>	<b>CSA C22.2 No.42</b>	<b>NOM</b>		
Plugs & Connectors Rated V-2 per UL 94		Receptacles Rated V-0 per UL 94		-40°C to 60°C	✓	✓	✓	Plugs & Connectors #E13393	Receptacles #E13399	#LR-406	#057



TYPE-EPTR	PLUG	NEMA PLUG	CONNECTOR w/ CLOSURE CAP	CORROSION RESISTANT RECEPTACLE, COVER, GASKET	CORROSION RESISTANT RECEPTACLE	NEMA RECEPTACLE
<b>20A 125V, 2-P 3-W, Grounding</b>						
Yellow EPTR	14W33	5-20P	15W33	60W33	5361-CR	5-20R
<b>20A 250V, 2-P 3-W, Grounding</b>						
Yellow EPTR	14W48	6-20P	15W48	60W48	5461-CR	6-20R
<b>20A 125V, 2-P 3-W, Grounding</b>						
Yellow EPTR	26W47	L5-20P	27W47	67W47	23CM-10	L5-20R
Black EPTR	26W47-B		27W47-B	See Below for Black Catalog No.		
<b>20A 250V, 2-P 3-W, Grounding</b>						
Yellow EPTR	26W48	L6-20P	27W48	67W48	23CM-20	L6-20R
<b>20A 277V, 2-P 3-W, Grounding</b>						
Yellow EPTR	26W49	L7-20P	27W49	67W49	23CM-30	L7-20R

CONNECTOR CAPS For Black Caps, Add Suffix -B	PLUG CAPS For Black Caps, Add Suffix -B	COVER w/ GASKET For Black Covers, Add Suffix -B	BLANK PLATE w/ GASKET	FD BOX GLASS-FILLED POLYESTER (2 KO Openings)
<b>Yellow</b> 15/20A Str. Blade & 15A Locking 50W50 20A Locking 50W52 30A Locking 50W54	<b>Yellow</b> 15/20A Str. Blade & 15A Locking 14W 20A Locking 26W 30A Locking 28W	<b>Yellow</b> 15/20A Str. Blade & 15A Locking 60W03 20A Locking 60W04 30A Locking 60W05	<b>Yellow</b> WP459	<b>Yellow</b> 1/2" 452CR 3/4" 453CR 1" 454CR



### Canadian Specifications:

15W16 — NEMA 15-20, 15 Amp 347V AC and 15W18 — NEMA 24-20, 20 Amp 347V AC are available. Please consult factory for availability.

