

30A 125V; 30A 250V

Industrial Grade



NEMA L5-30P



NEMA L5-30R



NEMA L6-30P



NEMA L6-30R

ELECTRICAL		
DIELECTRIC VOLTAGE	CURRENT INTERR.	TEMP. RISE
Withstands 2000V per UL 498	Full rated current	Max 30°C after 250 cycles of overload at 200% of rated current

MECHANICAL			
TERMINAL I.D.	TERMINAL ACCOMM.	PRODUCT I.D.	CORD GRIP RANGE
Brass, hot	#18 - #10 AWG	Ratings & NEMA I.D. permanently marked on device	.385" - .860"
Grounding	Receptacles #14 - #8 AWG		
White, neutral			
ENVIRONMENTAL			
FLAMMABILITY		OPERATING TEMP.	
Rated V-2 per UL 94		-40°C to 60°C	

STANDARDS & CERTIFICATIONS					
NEMA WD-6	ANSI C-73	UL 498	UL Fed Spec Listed WC-596	CSA C22.2 No.42	NOM
✓	✓	✓	#E13393 Plugs, Connectors & Flanged Inlets	#LR-406	#057
			#E13399 Receptacles & Flanged Outlets		



2621-B

2623

2620

2620-IG

2615

2616

TYPE	PLUG	CONNECTOR	SINGLE FLUSH RECEPTACLE	SINGLE FLUSH IG RECEPTACLE	FLANGED INLET	FLANGED OUTLET
30A 125V, NEMA L5-30P AND L5-30R, 2-P 3-W, Grounding						
Black & White	2611	2613	-	-	-	-
Yellow & White	2611-CY	2613-CY	-	-	-	-
All Black	2611-B	2613-B	2610	-	-	-
All White	-	-	-	-	2615	2616
Orange	-	-	-	2610-IG	-	-
Power Light Black & White	2611-PLC	2613-PLC	-	-	-	-
Power Light All Black	2611-PLB	2613-PLB	-	-	-	-
30A 250V, NEMA L6-30P AND L6-30R, 2-P 3-W, Grounding						
Black & White	2621	C2623	-	-	-	-
Yellow & White	2621-CY	C2623-CY	-	-	-	-
All Black	2621-B	C2623-B	2620	-	-	-
All White	-	-	-	-	2625F	2626F
Orange	-	-	-	2620-IG	-	-
Power Light Black & White	2621-PLC	2623-PLC	-	-	-	-

