

Plug Strips & Plug-Ins

3500, 4800 & 4900 Series - 15A 120V AC & 15A 125V AC Plug-In Devices



SPECIFICATIONS & FEATURES
3500, 4800 & 4900 SERIES
<ul style="list-style-type: none"> • Provides all mode protection for all outlets. • LED indicates protection is active.
STANDARDS & CERTIFICATIONS
ANSI/IEEE Categories A & B C-62.41 & C-62.45 UL 1449 #E146315 CSA #LR-94773

DESCRIPTION	CATALOG NO.	APPLICATION
3500, 4800 & 4900 Series		
6-Outlet Plug Strip, 6' Cord	4800-PS	All-Purpose
6-Outlet Plug Strip, 15' Cord	4800-S15	All-Purpose
6-Outlet Plug Strip, 6' Cord, No Switch	4800-PSN	All-Purpose
6-Outlet Surge Adapter, Beige	3500-P	Noise Attenuation for Micro-Processor Driven Equipment
6-Outlet Surge Adapter, w/ 2 RJ11 Phone Jacks	3500-PT	Noise Attenuation for Micro-Processor Driven Equipment
6-Outlet Surge Adapter, w/ 2F Coax Cable Connectors	3500-PC	Noise Attenuation for Micro-Processor Driven Equipment
6-Outlet Plug Strip, w/ 2 RJ11 Phone Jacks	4900-PST	Multi-Stage Protection
6-Outlet Surge Adapter, Beige	4900-P	Noise Attenuation for Micro-Processor Driven Equipment
6-Outlet Surge Adapter, w/ 2 RJ11 Phone Jacks	4900-PT	Noise Attenuation for Micro-Processor Driven Equipment
6-Outlet Surge Adapter, w/ 2F Coax Cable Connectors	4900-PC	Noise Attenuation for Micro-Processor Driven Equipment

CATALOG NO.	JOULES	UL 1449 (2nd Ed) IMPULSE 6kV/500A	MAX.SURGE CURRENT (test w/ 8x20us wave)	NOISE REJECTION	LOW VOLTAGE CLAMPING (UL 497A/B or UL 452)
3500, 4800 & 4900 Series					
4800-PS	540	L-N: 400V	L-N: 12kA	-5--40 dB (100K-30MHz)	-
4800-S15	540	L-N: 400V	L-N: 12kA	-5--40 dB (100K-30MHz)	-
4800-PSN	540	L-N: 400V	L-N: 12kA	-5--40 dB (100K-30MHz)	-
3500-P	540	L-N: 400V	L-N: 12kA	40 dB (150K-20MHz)	-
3500-PT	540	L-N: 400V	L-N: 12kA	40 dB (150K-20MHz)	-
3500-PC	540	L-N: 400V	L-N: 12kA	40 dB (150K-20MHz)	-
4900-PS	540	L-N: 400V	L-N: 12kA	-5--40 dB (100K-30MHz)	-
4900-PSC	540	L-N: 400V	L-N: 12kA	-5--40 dB (100K-30MHz)	-
4900-PST	540	L-N: 400V	L-N: 12kA	-5--40 dB (100K-30MHz)	265V
4900-P	540	L-N: 330V	L-N: 12kA	40 dB (150K-20MHz)	-
4900-PT	540	L-N: 330V	L-N: 12kA	40 dB (150K-20MHz)	-
4900-PC	540	L-N: 330V	L-N: 12kA	40 dB (150K-20MHz)	-