

15A 125V & 250V; 20A 125V & 250V



NEMA 5-15P



NEMA 5-15R



NEMA 6-15P



NEMA 6-15R



NEMA 5-20P



NEMA 5-20R



NEMA 6-20P



NEMA 6-20R

ELECTRICAL		
DIELECTRIC VOLTAGE	CURRENT INTERRUPT.	TEMP. RISE
Withstands 2000V per UL 498	Full rated current	Max 30°C after 250 cycles of overload at 200% of rated current

MECHANICAL			
TERMINAL I.D.	TERMINAL ACCOMM.	PRODUCT I.D.	CORD GRIP RANGE
Brass, hot Green, Grounding White, neutral	#18 - #10 AWG	Ratings & NEMA I.D. permanently marked on device	.245" - .700"
ENVIRONMENTAL			
FLAMMABILITY		OPERATING TEMP.	
Rated V-2 per UL 94		-40°C to 60°C	

STANDARDS & CERTIFICATIONS					
NEMA WD-6	ANSI C-73	UL 498	UL Fed Spec Listed WC-596	CSA C22.2 No. 42	NOM
✓	✓	✓	#E13393 Applies to Hospital Grade Versions Only	#LR-406	#057



5356-VB



5359-VB



5259-VY



5256-VA

TYPE	PYTHON PLUG	PYTHON CONNECTOR	PYTHON ANGLE PLUG
15A 125V, NEMA 5-15P AND 5-15R, 2-P 3-W			
Industrial Grade			
Black Yellow Gray	5256-VB 5256-VY 5256-VGY	5259-V 5259-VY 5259-VGY	- 5256-VA -
Hospital Grade			
White	8256-V	8259-V	-
15A 250V, NEMA 6-15P AND 6-15R, 2-P 3-W			
Industrial Grade			
Yellow	15656-VY	15659-VY	15656-VA
Hospital Grade			
White	8656-V	8659-V	-
20A 125V, NEMA 5-20P AND 5-20R, 2-P 3-W			
Industrial Grade			
Black Yellow	5356-VB 5356-VY	5359-VB 5359-VY	- 5356-VA
Hospital Grade			
White	8356-V	8359-V	-
20A 250V, NEMA 6-20P AND 6-20R, 2-P 3-W			
Industrial Grade			
Yellow	5456-VY	5459-VY	5456-VA
Hospital Grade			
White	8456-V	8459-V	-

