

Germany / Europe - Angle Mains Line Plugs, Side Cable Entry

Mains line plug with earthing contact, additional earthing socket and lateral cable entry point.

*Stecker mit seitlichem Schutzkontakt, zweitem Schutzkontaktsystem und seitlicher Kabeleinführung.*



533 WH

**SPECIFICATIONS**

- Electrical Ratings: 250V AC, 16A
- Standards according to: DIN VDE 0620-1:2005, DIN 49 441 Part 1
- Material & Type of Terminals: CuZn 37/39 (screw terminals)
- Material of Housing and Carrying Parts: Polypropylene
- RoHS COMPLIANT 2002/96/EC

Catalog No.	Color	Description	VPE/Pack	EDP-No.
533 WH	White	Angle Mains Line Plug	50	124936
533 WHI	Ivory	Angle Mains Line Plug (electrical white)	50	124637
533 BK	Black	Angle Mains Line Plug	50	124638

**Notes:** Rewireable, for supply line H05VV-F 3 x 1,0 mm<sup>2</sup>, 3 x 1,5 mm<sup>2</sup> and 3 x 2,5 mm<sup>2</sup> max.

*Wiederanschließbare Ausführung für flexible Leiter H05VV-F 3 x 1,0 mm<sup>2</sup>, 3 x 1,5 mm<sup>2</sup> und 3 x 2,5 mm<sup>2</sup> max.*

