



Part Number: **UC-871**

Configuration: according BS 546, SABS 164/1991

Description: Old Style British Grounding Plug

Ratings: BS 15A/250V, SABS 16A/250V

Wire Type(s): H03VV-F 3G 0.75 mm<sup>2</sup>  
 H03VV-F 2 x 0.75 mm<sup>2</sup>  
 H05VV-F 3G 0.75 mm<sup>2</sup>  
 H05VV-F 2 x 0.75 mm<sup>2</sup>  
 H05VV-F 3G 1.0 mm<sup>2</sup>  
 H05VV-F 2 x 1.0 mm<sup>2</sup>  
 H05VV-F 3G 1.5 mm<sup>2</sup>  
 H05VV-F 2 x 1.5 mm<sup>2</sup>  
 H03RT-F 3G 0.75 mm<sup>2</sup>  
 H03RT-F 2 x 0.75 mm<sup>2</sup>  
 H03RT-F 3G 1.0 mm<sup>2</sup>  
 H03RT-F 2 x 1.0 mm<sup>2</sup>  
 H03RT-F 3G 1.5 mm<sup>2</sup>  
 H03RT-F 2 x 1.5 mm<sup>2</sup>

Features: Molded PVC male grounding plug with inner housing, angle, with flex strain relief. Standard brass solid round pins.