


3-Conductor Hospital Grade Power Supply



Molded PVC Hospital Grade
Grounding Plug
NEMA 5-15P UC-018



Remove Outer Jacket 2"
Strip and Twist 5/8"

TYPE SJT



PVC Jacketed, 60°C/105°C, VW-1

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH Ft/Mtrs.	NOM. O.D. Inches	STD. PKG.	PKG. WT. lbs.
4880-03M-BB	10A-125V	18/3(41x34)	NA	9.8/3.0	.307	50	34
4800-03M-GG	10A-125V	18/3(41x34)	NA	9.8/3.0	.307	50	34
4881-03M-GG*	10A-125V	18/3(41x34)	NA	9.8/3.0	.307	50	34
4680-04M-BB	13A-125V	16/3(26x30)	NA	13.2/4.0	.334	50	34
4680-04M-GG	13A-125V	16/3(26x30)	NA	13.2/4.0	.334	50	34
4480-04M-GG	15A-125V	14/3(41x30)	NA	13.2/4.0	.375	25	30

* Denotes clear PVC male plug

Coiled and tied, individually polybagged



Molded PVC Hospital Grade
Grounding Plug
NEMA 5-15P UC-018A



Remove Outer Jacket 2"
Strip and Twist 5/8"

TYPE SJT



PVC Jacketed, 60°C/105°C, VW-1

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH Ft/Mtrs.	NOM. O.D. Inches	STD. PKG.	PKG. WT. lbs.
4870-03M-GG	10A-125V	18/3(41x34)	NA	9.8/3.0	.307	50	38

Coiled and tied, individually polybagged

Green dot on face of plug designates approval for hospital grade use.

U-shaped grounding pin is used on hospital grade plugs.

Also available with low leakage cable as custom item.