


3-Conductor Hospital Grade Detachable Power Supply



Molded PVC Hospital Grade
Grounding Plug
NEMA 5-15P UC-018



Molded PVC
Receptacle
IEC 60320/C13 UC-005

TYPE SJT



PVC Jacketed, 60°C /105°C, VW-1

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH Ft/Mtrs.	NOM. O.D. Inches	STD. PKG.	PKG. WT. lbs.
4810-03M-BB	10A-125V	18/3(41x34)	NA	9.8/3.0	.307	50	40
4810-03M-GG	10A-125V	18/3(41x34)	NA	9.8/3.0	.307	50	40
4811-03M-GG*	10A-125V	18/3(41x34)	NA	9.8/3.0	.307	50	40

Coiled and tied, individually polybagged.



Molded PVC Hospital Grade
90° Grounding Plug
NEMA 5-15P UC-018A



Molded PVC
Receptacle
IEC 60320/C13 UC-005

TYPE SJT



PVC Jacketed, 60°C /105°C, VW-1

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH Ft/Mtrs.	NOM. O.D. Inches	STD. PKG.	PKG. WT. lbs.
4820-03M-GG	10A-125V	18/3(41x34)	NA	9.8/3.0	.307	50	44
4622-04M-BB**	13A-125V	16/3(26x30)	NA	13.2/4.0	.334	25	32

Coiled and tied, individually polybagged.

* Denotes clear PVC male plug

** Denotes clear PVC male plug with built-in lamp for added safety (UC-018AL).

Green dot on face of plug designates approval for hospital grade use.

U-shaped grounding pin is used on hospital grade plugs.

Also available with low leakage cable as custom item.