

Heavy Duty Safety Switches

Special Application – Receptacle Switches

Class 3110



H362AWA
Interlocked Receptacle
Switch with Appleton
POWER TITE Receptacle

Receptacle Switches

Interlocked Receptacle Switches are furnished with a factory installed 3 Phase 4 Wire Appleton POWER TITE®, Crouse-Hinds Style 2 ARKTITE®, or HUBBELLOCK® receptacle. The fourth wire is connected to the switch equipment ground terminal and is not a neutral termination. Interlocking linkage between the receptacle and switch mechanism prevents insertion or removal of the plug while the switch is in the "ON" position or insertion of any plug other than specified. Ground lugs are included.

Appleton POWER TITE Receptacle

- Devices are UL Listed and CSA Certified, suitable for use as service equipment.
- Receptacles are epoxy powder coated over copper-free cast aluminum and NEMA 3, 3R, 4, 4X and 12 rated. Appleton receptacles are UL Classified for use with Crouse-Hinds plugs listed below.
- Short circuit rating: 10,000 amperes when used in conjunction with Class H or K fuses.
200,000 amperes when used in conjunction with Class R or J fuses.

Amps	NEMA 1		NEMA 3, 3R, 4, 4X, 5, 12 (Stainless Steel Enclosure)		NEMA 3, 3R, 4, 4X, 12 Cast Aluminum Enclosure		NEMA 12, 3R		Use With Plug ■		Horsepower Ratings—3Ø★					
	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	480 Vac		600 Vac	250 Vdc▲		
											Std.	Max.	Std.	Max.		
Fusible—3-Pole, 600 Vac, 250 Vdc																
30	H361WA		H361DSWA		H361CSWA		H361AWA		ACP3034BC		5	15	7½	20	5	—
60	H362WA		H362DSWA		H362CSWA		H362AWA		ACP6034BC		15	30	15	50	10	—
100	H363WA		H363DSWA		H363CSWA		H363AWA		ACP1034CD		25	60	30	75	20	—
Not Fusible—3-Pole, 600 Vac, 250 Vdc																
30	HU361WA		HU361DSWA		HU361CSWA		HU361AWA		ACP3034BC		—	20	—	30	—	5
60	HU362WA		HU362DSWA		HU362CSWA		HU362AWA		ACP6034BC		—	50	—	60	—	10
100	HU363WA		HU363DSWA		HU363CSWA		HU363AWA		ACP1034CD		—	75	—	100	—	20



H362AWC
Interlocked Receptacle
Switch with Crouse-Hinds
ARKTITE Receptacle

Crouse-Hinds ARKTITE Receptacle

- UL Listed suitable for use as service equipment.
- Short circuit rating: 10,000 amperes when used in conjunction with Class H or K fuses.
200,000 amperes when used in conjunction with Class R or J fuses.

Amps	NEMA 1		NEMA 3, 3R, 4, 4X, 5, 12 (Stainless Steel Enclosure)		NEMA 12, 3R		Use With Plug		Horsepower Ratings—3Ø★			
	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	480 Vac		600 Vac	
									Std.	Max.	Std.	Max.
Fusible—3-Pole, 600 Vac Maximum												
30	H361WC		H361DSWC		H361AWC		APJ3485		5	15	7½	20
60	H362WC		H362DSWC		H362AWC		APJ6485		15	30	15	50
100	H363WC		H363DSWC		H363AWC		APJ10487		—	60	—	75
Not Fusible—3-Pole, 600 Vac Maximum												
30	HU361WC		HU361DSWC		HU361AWC		APJ3485		—	20	—	30
60	HU362WC		HU362DSWC		HU362AWC		APJ6485		—	50	—	60
100	HU363WC		HU363DSWC		HU363AWC		APJ10487		—	60	—	100

HUBBELLOCK Receptacle

UL Listed, suitable for use as service equipment.

- Short circuit rating: 10,000 amperes

Note: The Hubbellock receptacle switch utilizes the SQUARE D interlocked plug SD12781 only available from Square D.

Amps	NEMA 1		NEMA 12		Use With Plug		Horsepower Ratings—3Ø★			
	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	480 Vac		600 Vac	
							Std.	Max.	Std.	Max.
Fusible—3-Pole, 600 Vac Maximum										
60	H362WH		H362AWH		SD12781 ♦		15	30	15	50
Not Fusible—3-Pole, 600 Vac Maximum										
60	HU362WH		HU362AWH		SD12781 ♦		—	50	—	60

- ▲ For switching DC, use two switching poles.
- ♦ Receptacle UL Listed for use with "Appleton ACP or CPH" plugs; UL Classified for use with Crouse-Hinds "APJ" ARKTITE plugs listed on this page.
- HUBBELL plug is furnished with a Kellems grip for 1½" to 1¾" cable diameter.
- ★ Std.—Using fast acting one time fuses. Max.—Using dual element time delay fuses.



H362AWH
Interlocked Receptacle
Switch with Hubbell
Hubbellock Receptacle

Accessories pages 3-9 through 3-11