

Thermal-magnetic Molded Case Circuit Breakers

250, 400 Ampere Frame

Class 655, 825, 660



KAL/KHL
2- and 3-pole
70–250 Amperes



KIL36250



Q4-L
2- and 3-pole
250–400 Amperes

K-frame—250 A, Thermal-magnetic (600 Vac)

Continuous Current Rating @ 40° C	AC Magnetic Trip Settings▲		Standard Interrupting		High Interrupting		Current Limiting		Terminal Wire Range
	Low	High	Catalog Number	Price	Catalog Number	Price	Catalog Number	Price	
2-pole, 600 Vac, 250 Vdc									
70	350	700	KAL26070		KHL26070		AL250KA (1) #4 AWG–350 kcmil
80	400	800	KAL26080		KHL26080		
90	450	900	KAL26090		KHL26090		
100	500	1000	KAL26100		KHL26100		
110	550	1100	KAL26110		KHL26110		KIL26110	...	
125	625	1250	KAL26125		KHL26125		KIL26125	...	
150	750	1500	KAL26150		KHL26150		KIL26150	...	
175	875	1750	KAL26175		KHL26175		KIL26175	...	
200	1000	2000	KAL26200		KHL26200		
225	1125	2250	KAL26225		KHL26225		
250	1250	2500	KAL26250		KHL26250		
200	1000	2000	KIL26200	...	AL250KI (1) #1/0 AWG–350 kcmil
225	1125	2250	KIL26225	...	
250	1250	2500	KIL26250	...	
3-pole, 600 Vac, 250 Vdc									
70	350	700	KAL36070		KHL36070		AL250KA (1) #4 AWG–350 kcmil
80	400	800	KAL36080		KHL36080		
90	450	900	KAL36090		KHL36090		
100	500	1000	KAL36100		KHL36100		
110	550	1100	KAL36110		KHL36110		KIL36110	...	
125	625	1250	KAL36125		KHL36125		KIL36125	...	
150	750	1500	KAL36150		KHL36150		KIL36150	...	
175	875	1750	KAL36175		KHL36175		KIL36175	...	
200	1000	2000	KAL36200		KHL36200		
225	1125	2250	KAL36225		KHL36225		
250	1250	2500	KAL36250		KHL36250		
200	1000	2000	KIL36200	...	AL250KI (1) #1/0 AWG–350 kcmil
225	1125	2250	KIL36225	...	
250	1250	2500	KIL36250	...	

K-frame—250 A, Thermal-magnetic (480 Vac)

Continuous Current Rating @ 40° C	AC Magnetic Trip Settings▲		Extra High Interrupting		Terminal Wire Range
	Low	High	Catalog Number	Price	
2-pole, 480 Vac					
110	550	1100	KCL24110		AL250KA (1) #4 AWG–350 kcmil
125	625	1250	KCL24125		
150	750	1500	KCL24150		
175	875	1750	KCL24175		
200	1000	2000	KCL24200		AL250KI (1) #1/0 AWG–350 kcmil
225	1125	2250	KCL24225		
250	1250	2500	KCL24250		
3-pole, 480 Vac					
110	550	1100	KCL34110		AL250KA (1) #4 AWG–350 kcmil
125	625	1250	KCL34125		
150	750	1500	KCL34150		
175	875	1750	KCL34175		
200	1000	2000	KCL34200		AL250KI (1) #1/0 AWG–350 kcmil
225	1125	2250	KCL34225		
250	1250	2500	KCL34250		

Q4-frame—400 A, Thermal-magnetic (240 Vac)

Continuous Current Rating @ 40° C	AC Magnetic Trip Settings▲		Standard Interrupting		Terminal Wire Range
	Low	High	Catalog Number	Price	
2-pole, 240 Vac					
250	1250	2500	Q4L2250		AL400LA (1) #1 AWG-600 kcmil or (2) #1 AWG-250 kcmil
300	1500	3000	Q4L2300		
350	1750	3500	Q4L2350		
400	2000	4000	Q4L2400		
3-pole, 240 Vac					
250	1250	2500	Q4L3250		AL400LA (1) #1 AWG-600 kcmil or (2) #1 AWG-250 kcmil
300	1500	3000	Q4L3300		
350	1750	3500	Q4L3350		
400	2000	4000	Q4L3400		

Interrupting Ratings (kA)

	KAL	KHL	KCL	KIL	Q4
240 V	42	65	100	200	25
480 V	25	35	65	200	...
600 V	22	25	...	100	...

▲ UL magnetic trip setting tolerances are ±25% (low) and ±20% (high) from nominal values shown.

Accessories pages 6-36–6-38
 Optional Lugs pages 6-43, 6-44
 Dimensions pages 6-49, 6-50
 Enclosures pages 6-51–6-54